


## Stainless Steel Forged Fittings NPT & 45° Tee



45° 三通TEE

Type: Forged Fittings & 45° Tee

Size: 1/8"-4"

尺寸单位为毫米 Dimensions in Millimeters.

公称管子规格		螺纹外接头端 到端 End to End Couplings W	管帽端到端 End to End Caps P		外径 Outside Diameter D		螺纹端部壁厚 End Wall Thickness G(Min.)		螺纹长度 Length of Thread.(Min)(1)	
DN	Nom. Pipe Size		3000&6000	3000	6000	3000	6000	3000	6000	B
6	1/8	32	19	—	16	22	4.8	—	6.4	6.7
8	1/4	35	25	27	19	25	4.8	6.4	8.1	10.2
10	3/8	38	25	27	22	32	4.8	6.4	9.1	10.4
15	1/2	48	32	33	28	38	6.4	7.9	10.9	13.6
20	3/4	51	37	38	35	44	6.4	7.9	12.7	13.9
25	1	60	41	43	44	57	9.7	11.2	14.7	17.3
32	1-1/4	67	44	46	57	64	9.7	11.2	17.0	18.0
40	1-1/2	79	44	48	64	76	11.2	12.7	17.8	18.4
50	2	86	48	51	76	92	12.7	15.7	19.0	19.2
65	2-1/2	92	60	64	92	108	15.7	19.0	23.6	28.9
80	3	108	65	68	108	127	19.0	22.4	25.9	30.5
100	4	121	68	75	140	159	22.4	28.4	27.7	33.0

Standard: ASTM A-182/ANSI/DIN/MSS-SP-97/ JIS B2316

Pressure: ANSI B16.11 CLASS 3000Lbs、 6000Lbs、 9000Lbs

Socket welded connection according to ANSI B16.11

---

NPT threaded connection according to ANSI B2.1

Material: Stainless steel F304L,310S, F316L,317L, F347,904L, S31803, S32750,254SMO, Inconel 625

Product link : <https://www.triround-inox.com/stainless-steel-forged-fittings-npt-45-tee.html>