

# Stainless Steel Butt-Welding Fittings Tee ASME/ANSI B16.28



## Tee (Equal Tee, Reduced Tee)

### Executive Standard:

ASME/ANSI B16.9, ASME/ANSI B16.28, MSS-SP-43, MSS-SP-75,

DIN2605, JIS B2311/2312/2313, GB12459, GB/T13401, SH3408, SH3409, ISO 3419, ISO 5251, HG/T21635, HG/T21631 etc.

· Material:

WP304, WP304L, WP304/304L WP310S, WP316, WP316L, WP316/WP316L, WP317L, WP321, WP321H, WP347, WP347H, 904L,

S31803, S32750, S31760, S31254, INCONEL 625

Dimension:

Nominal Pipe Size (NPS)	DN	Outside Diameter of Barrel		Long Pattern Length, <i>F</i> [Notes (3), (4)]	Short Pattern Length, <i>F</i> [Notes (3), (4)]	Radius of Fillet, <i>R</i> [Note (5)]	Diameter of Lap, <i>G</i> [Note (6)]
		Max.	Min.				
1/2	15	22.8	20.5	76	51	3	35
3/4	20	28.1	25.9	76	51	3	43
1	25	35.0	32.6	102	51	3	51
1 1/4	32	43.6	41.4	102	51	5	64
1 1/2	40	49.9	47.5	102	51	6	73
2	50	62.4	59.5	152	64	8	92
2 1/2	65	75.3	72.2	152	64	8	106
3	80	91.3	88.1	152	64	10	127
3 1/2	90	104.0	100.8	152	76	10	140
4	100	116.7	113.5	152	76	11	157
5	125	144.3	140.5	203	76	11	185
6	150	171.3	167.5	203	89	13	218
8	200	222.1	218.3	203	102	13	270
10	250	277.2	272.3	254	127	13	324
12	300	328.0	323.1	254	152	13	381
14	350	359.9	354.8	305	152	13	413
16	400	411.0	405.6	305	152	13	470
18	450	462	456	305	152	13	533
20	500	514	507	305	152	13	584
22	550	565	558	305	152	13	641
24	600	616	609	305	152	13	692

Seamless: 1/2" to 20" (DN15 ~DN500)

---

Welded: 1/2" to 48" (DN15~DN1200)

· Wall Thickness: SCH5S to SCH160 XS, XXS

· Process: Cold & Mandrel Forming

Product

link :

<https://www.triround-inox.com/stainless-stgeel-butt-welding-fittings-tee-asmeansi-b16-28.html>