


W/N flange -F53/S32750/2507.HASTELLOY C-276



W/N flange -F53/S32750/2507.HASTELLOY C-276

Normal Pipe Size	Depth of Socket	DRILLING			BOLTING				APPROXIMATE WEIGHT				
		Bolt Circle Diam	Number of Holes	Diam of Holes	Diam of Bolts (inch)	Machine Bolt Length	Stud Bolt Length		Welding Neck	Slip-on and Threaded	Lap Joint	Blind	Socket Welding
	Y						Raised Face	Raised Face					
1/2	9.7	60.5	4	15.7	1/2	50.8	57.2	-	0.52	0.47	0.51	0.47	0.47
3/4	11.2	69.9	4	15.7	1/2	50.8	63.5	-	0.92	0.75	0.70	0.63	0.76
1	12.7	79.2	4	15.7	1/2	57.2	63.5	76.2	1.10	0.86	0.93	0.95	0.87
1 1/4	14.2	88.9	4	15.7	1/2	57.2	69.9	82.6	1.40	1.40	1.40	1.40	1.43
1 1/2	15.7	98.6	4	15.7	1/2	63.5	69.9	82.6	1.81	1.41	1.51	1.62	1.45
2	17.5	120.7	4	19.1	5/8	69.9	82.6	95.3	2.8	2.26	2.38	2.64	2.33
2 1/2	19.1	139.7	4	19.1	5/8	76.2	88.9	101.6	4.28	3.43	3.60	4.06	3.55
3	50.6	152.4	4	19.1	5/8	76.2	88.9	6	5.18	4.00	4.04	5.00	4.15
3 1/2	22.4	177.8	8	19.1	5/8	76.2	88.9	101.6	5.50	5.00	4.99	5.90	5.00
4	23.9	190.5	8	19.1	5/8	76.2	88.9	101.6	7.32	5.75	5.96	7.50	5.99
5	23.9	215.9	8	22.4	3/4	82.6	95.3	6	8.91	6.51	6.44	9.00	6.96
6	26.9	241.3	8	22.4	3/4	82.6	101.6	108.0	11.26	7.81	7.70	12.00	8.41
8	31.8	298.5	8	22.4	3/4	88.9	108.0	120.0	18.00	13.00	12.66	20.00	13.93
10	33.3	362.0	12	25.4	7/8	101.6	114.3	7	25.00	17.10	17.00	0	19.50
12	39.6	431.8	12	25.4	7/8	101.6	120.7	127.0	38.98	27.68	28.30	30.00	29.03
								133.4				44.00	

14	41.4	476.3	12	28.4	1	114.3	133.4	146.	51.71	35.20	41.50	64.0	38.56
16	44.5	539.8	16	28.4	1	114.3	133.4	1	64.41	45.00	52.98	0	47.37
18	49.3	577.9	16	31.8	11/8	127.0	146.1	146.	74.84	54.00	68.00	78.0	58.72
								1				0	
								158.				95.0	
								8				0	
20	54.1	635.0	20	31.8	11/8	139.7	158.8	171.	89.36	73.00	85.00	125.	77.81
24	63.5	749.3	20	35.1	11/4	152.4	171.5	5	119.66	96.00	120.0	00	100.7
								184.			0	190.	5
								2				00	

Product link : <https://www.triround-inox.com/wn-flange-f53s327502507-hastelloy-c-276.html>