


# Stainless Steel Forged Fittings NPT & Half Coupling



单承管箍HALF COUPLING

Type: Forged Fittings& Half Coupling

Size: 1/8"-4"

尺寸单位为毫米 Dimensions in Millimeters.

| 公称管子规格 |                      | 螺纹外接头端<br>到端<br>End to End<br>Couplings W | 管帽端到端<br>End to End<br>Caps P |      | 外径<br>Outside<br>Diameter D |      | 螺纹端部壁厚<br>End Wall<br>Thickness G(Min.) |      | 螺纹长度<br>Length of<br>Thread.(Min)(1) |      |
|--------|----------------------|-------------------------------------------|-------------------------------|------|-----------------------------|------|-----------------------------------------|------|--------------------------------------|------|
| DN     | Nom.<br>Pipe<br>Size | 3000&6000                                 | 3000                          | 6000 | 3000                        | 6000 | 3000                                    | 6000 | B                                    | L2   |
| 6      | 1/8                  | 32                                        | 19                            | —    | 16                          | 22   | 4.8                                     | —    | 6.4                                  | 6.7  |
| 8      | 1/4                  | 35                                        | 25                            | 27   | 19                          | 25   | 4.8                                     | 6.4  | 8.1                                  | 10.2 |
| 10     | 3/8                  | 38                                        | 25                            | 27   | 22                          | 32   | 4.8                                     | 6.4  | 9.1                                  | 10.4 |
| 15     | 1/2                  | 48                                        | 32                            | 33   | 28                          | 38   | 6.4                                     | 7.9  | 10.9                                 | 13.6 |
| 20     | 3/4                  | 51                                        | 37                            | 38   | 35                          | 44   | 6.4                                     | 7.9  | 12.7                                 | 13.9 |
| 25     | 1                    | 60                                        | 41                            | 43   | 44                          | 57   | 9.7                                     | 11.2 | 14.7                                 | 17.3 |
| 32     | 1-1/4                | 67                                        | 44                            | 46   | 57                          | 64   | 9.7                                     | 11.2 | 17.0                                 | 18.0 |
| 40     | 1-1/2                | 79                                        | 44                            | 48   | 64                          | 76   | 11.2                                    | 12.7 | 17.8                                 | 18.4 |
| 50     | 2                    | 86                                        | 48                            | 51   | 76                          | 92   | 12.7                                    | 15.7 | 19.0                                 | 19.2 |
| 65     | 2-1/2                | 92                                        | 60                            | 64   | 92                          | 108  | 15.7                                    | 19.0 | 23.6                                 | 28.9 |
| 80     | 3                    | 108                                       | 65                            | 68   | 108                         | 127  | 19.0                                    | 22.4 | 25.9                                 | 30.5 |
| 100    | 4                    | 121                                       | 68                            | 75   | 140                         | 159  | 22.4                                    | 28.4 | 27.7                                 | 33.0 |

Standard: ASTM A-182/ANSI/DIN/MSS-SP-97/ JIS B2316

Pressure: ANSI B16.11 CLASS 3000Lbs、 6000Lbs、 9000Lbs

Socket welded connection according to ANSI B16.11

---

NPT threaded connection according to ANSI B2.1

Material: Stainless steel F304L,310S, F316L,317L, F347,904L, S31803, S32750,254SMO, Inconel 625

Product

link : <https://www.triround-inox.com/stainless-steel-forged-fittings-npt-half-coupling.html>