


Threaded flange-F51/S31803/S2205,F53/S32750/2507



Threaded flange-F51/S31803/S2205,F53/S32750/2507

Normal Pipe Size	Depth of Socket	DRILLING			BOLTING				APPROXIMATE WEIGHT				
		Bolt Circle Diam	Number of Holes	Diam of Holes	Diam of Bolts (inch)	Machine Bolt Length			Welding Neck	Slip-on and Threaded	Lap Joint	Blind	Socket Welding
	Y					Raised Face	Raised Face	Ring Joint					
1/2	9.7	66.5	4	15.7	1/2	57.2	63.5	76.2	0.80	0.62	0.61	0.65	0.62
3/4	11.2	82.6	4	19.1	5/8	63.5	76.2	88.9	1.40	1.30	1.30	1.40	1.34
1	12.7	88.9	4	19.1	5/8	63.5	76.2	88.9	1.64	1.50	1.50	1.50	1.55
1 1/4	14.2	98.6	4	19.1	5/8	69.9	82.6	95.3	2.10	1.70	1.70	2.80	1.76
1 1/2	15.7	114.3	4	22.4	3/4	76.2	88.9	101.6	3.06	2.60	2.60	2.80	2.69
2	17.5	127.0	8	19.1	5/8	76.2	88.9	101.6	3.50	3.00	3.00	3.30	3.14
2 1/2	19.1	149.4	8	22.4	3/4	82.6	101.6	114.3	5.31	4.50	4.50	5.40	4.74
3	50.6	168.1	8	22.4	3/4	88.9	108.0	120.7	7.32	5.90	5.80	7.00	6.29
3 1/2	22.4	184.2	8	22.4	3/4	95.3	108.0	127.0	8.2	7.72	7.72	9.53	
4	23.9	200.2	8	22.4	3/4	95.3	114.3	127.0	11.30	10.13	10.07	12.00	
5	23.9	235.0	8	22.4	3/4	108.0	120.7	133.4	15.12	13.00	13.00	16.00	
6	26.9	269.7	12	22.4	3/4	108.0	120.7	139.7	20.00	17.00	16.00	22.00	
8	31.8	330.2	12	25.4	7/8	120.7	139.7	152.4	30.48	26.00	25.00	36.00	
10	33.3	387.4	16	28.4	1	139.7	158.8	171.5	43.74	34.16	39.92	55.34	
12	39.6	450.9	16	31.8	1 1/8	146.1	171.5	184.2	64.41	51.26	60.00	80.00	
14	41.4	514.4	20	31.8	1 1/8	158.8	177.8	190.5	88.30	75.00	85.00	110.0	
16	44.5	571.5	20	35.1	1 1/4	165.1	190.5	203.2	115.00	94.00	112.0	0	
18	49.3	628.7	24	35.1	1 1/4	171.5	196.9	209.6	143.00	109.00	0	139.2	
											135.0	5	
											0	178.0	
											0	0	
20	54.1	685.8	24	35.1	1 1/4	184.2	203.2	222.3	175.00	136.00	165.0	223.1	
24	63.5	812.8	24	41.1	1 1/2	203.2	228.6	254.0	260.00	245.00	0	7	
											250.0	355.0	
											0	0	

Note : Customer's demands about products are considered.

Product

link : <https://www.triround-inox.com/threated-flange-f51s31803s2205f53s327502507.html>